## RETSOL **D-5030+** Read 1D & 2D Barcodes



## **Key Features**

- » Ergonomic and Sleek Design
- » Read all Mainstream 1D & 2D Barcodes
- » Low Power Consumption, Strong Decoding
- » Built in USB Interface
- » Mobile Screen LCD/LED Barcode Reading

## Applications

Ideal for Retail, Theater, e-Business, Hospital, Logistics and industrial environments.



## **Technical Specification**

Performance	Parameters
-------------	------------

Image (Pixels) 640 Pixels (H) x 480 Pixels (V)

Aiming: 617nm LED; Illumination: 625nm LED **Light Source** 

Field of View 42° (H) x 31.5° (V)

Scan Precision

25% Minimum reflective difference **Print Contrast** 

Motion Tolerance up to 5M per second

Interfaces USB, RS232

**Physical Parameters** 

**Dimensions** 170mm x 70mm x 95mm

Weight 126g 5V DC ± 10% Voltage Current 400mA(Operating)

Symbology Decode Capability

1D Codebar, Code 11, Code 39, Code 93, UPCA, UPCE, EAN13,

> Code 128, Interleaved 2 of 5, Matrix 2 of 5, MSI Code, Gs1 Databar. PDF417, MicroPDF417, Data Matrix, QR Code, MicroQR, Aztec, Hanxin

User Environment

**Operating Temperature** 0°C to 50°C Storage Temperature -40°C to 70°C

Humidity 0% to 95% Relative humidity, non-condensing **Shock Specification** Designed to withstand 1.5m (5 feet Drops)

**IP Rating** IP42


Warranty

2D

Warranty 2 Year - Factory Warranty \*



#33, Thiruveedhi Amman Koil Street, Ramakrishna Nagar, Raja Annamalaipuram, Chennai - 600 028, Tamilnadu, India



**T** 044 2461 6222/6277, 2495 3936, +91 944264493



