


RETSOL RTP-80UES

Thermal Receipt Printer



Key Features:

• Versatile Media Support

Supports 58mm, 80mm, and 83mm paper widths.

• Simplified Maintenance

Designed for easy access and hassle-free upkeep.

• Smart Cutter Technology

Reliable auto-cutter features intelligent anti-jamming code.

• Broad Compatibility

Fully compatible with standard ESC/POS commands.

• Rapid Updates

Supports IAP firmware updates in under 5 seconds.



RTP-80UES

Technical Specifications

Resolution	203 DPI
Printing method	Direct thermal
Paper width	83mm
Print width	72mm
Column capacity	576 dots/line
Interface	USB+LAN+SERIAL
Printing Speed	260mm/s
Line spacing	3.75mm (Adjustable by commands)
Paper type	Continuous paper
Paper thickness	0.06mm - 0.08mm
Paper roll outer diameter	83mm±0.5mm
Character size	ANK, Font A: 1.5×3.0mm(12×24 dots) Font B: 1.1×2.1mm(9×17 dots)
ID Barcode	UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODE39/ITF/CODABAR/CODE93/CODE128
2D Barcode	QR CODE/PDF417
NV Flash	256 Kbytes
Power adaptor	Input: AC 100~240V, 50~60Hz
Printer input	DC 24V/2.5A
Cash drawer	DC 24V/1A
Weight	0.9Kg
Dimensions	134 x 130 x 132mm (D*W*H)
Work environment	Temperature (0~45°C) humidity(10~80°C)
Storage environment	Temperature (-10~60°C) humidity(10~90°C)
Emulation	ESC/POS
Driver	Windows/Linux/Mac/Android

* Warranty - Against Manufacturing Defects on the Printer
Specifications are subject to change without notice

