

RETSOL RPS-7013

POS TERMINAL

Features

- Capacitive multi-point touch screen.
- Cable management friendly design.
- Abundant interfaces better connectivity.
- Rich interface to support more peripherals



RPS-7013	Technical Specification
CPU	Intel® Core™ i3-1215U
GPU	Intel Graphics
RAM	8 GB Memory Stick; Optional up to 16GB
ROM	256 GB SSD
O.S Supports	Windows 11, Windows 10, Linux Debian
Touch Panel	15" 3 points capacitive touch panel
Primary Display	15" TFT-LCD panel, 1024*768 (max.)
Secondary Display (optional)	11.6" TFT-LCD Screen / 9.7" TFT-LCD Screen VFD 20 Character * 2 Line
Ports	1*AUDIO, 1*COM, 6*USB, 1*LAN, 1*HDMI, 1*DC, 1*RJ48, 1*RJ11, 1*USB TYPE-C, WIFI, BLUETOOTH
Optional Peripherals	MSR, Dallas Key
Power adapter	24V Adapter
Environment	Operating Temperature: 0°C-60°C Storage Temperature: -20°C-75°C Humidity: 0%-95% Rh without condensation

* Warranty - Against Manufacturing Defects on the POS Machine
Specifications are subject to change without prior notice

